

SPCBZ-4



Envasadora tapadora Líquidos



Description:

The machine is a four-head ceramic pump liquid three-use (filling, lid-revolving and lid-rolling) machine. It uses the ceramic injection cylinder to fill, anti-corrosive, abrasion resistant, high measurement precision, and long use life-expectancy. It is widely used in the filling of the thin and viscous liquid for the industry of foodstuff, pharmacy, cosmetics and pesticide. It may be used in lid-revolving and the aluminum-lid's rolling, one machine multi-use, it has the merits of fast filling speed, non-drop and convenient cleaning.

1. Features

- 1.1 Using volume ceramic pump to fill, high precision and large range of adjusting volume.

ALLENDE Y COMPAÑIA LIMITADA

SANTA ROSA 1177 – B (56 2) 5515302 Santiago-Chile www.maspack.cl ventas@maspack.cl



1.2 The ceramic pump filling system doesn't adsorb the medicine, its chemical stability good, high temperature resistant, anti-corrosive, abrasion resistant, long use life-expectancy, has a unique advantage for filling some corrosive medicine liquid.

1.3 Automatically stopping the machine as lacking bottle and toppling bottle, not to fill as lacking bottle.

1.4 The filling system set the water-shrinking function, non-drop.

1.5 Suiting for the filling of different viscous liquid.

1.6 The filling needle-head descends into the bottle bottom to fill. Slowly goes up, so that preventing to bubble.

1.7 The magnetic moment lid-revolving head, its degree of tightness may be adjusted at will.

2. Technological parameters

2.1 Production speed 2000-2500bottles/hour

2.2 Sizes <150ml

2.3 Measurement error $\pm 1\%$

2.4 Production capacity 2000-2500bottles/hour

2.5 Acceptance rate of lid-revolving 99%

2.6 Machine power 1.2kw

2.7 Voltage 380V

2.8 Contour sizes 2500×850×1600mm

2.9 Net weight 600kg

2 Price for the machine

Name of machine	Type	Description of machine	Unit price(USD)
FOUR-HEAD CERAMIC PUMP STARIGHT LIQUID THREE-USE (FILLING LID-REVOLVING AND LID-ROLLING) MACHINE	SPCBZ-4	1 Production speed 1000-2000bottles/h 2 Sizes <150ml 3 Measurement error $\pm 1\%$ 4 Production capacity 2000- 2500bottles/h 5 Acceptance rate of lid-revolving 99% 6 Machine power 1.2kw 7 Voltage 380V 8 Contour sizes 2500×850×1600mm 9 Net weight 600kg	23.600

ALLENDE Y COMPAÑIA LIMITADA

SANTA ROSA 1177 – B (56 2) 5515302 Santiago-Chile www.maspack.cl ventas@maspack.cl