



SPZP26-XX Battery powered automatic high tension plastic strapping tool

The most powerful, reliable battery powered plastic strapping tool at the most attractive price.



- > Adjustable tension, maximum 330kgs (3300N) for heavy duty strapping jobs.
- > 14.4V 3000mAh NiMH high capacity rechargeable battery.
- > BOSCH 30 minutes charger.
- > High friction-weld sealing efficiency, no metal seals required.
- > Adjustable sealing time for various strap specifications.
- > Ergonomic design and excellent weight distribution to reduce hand fatigue.
- > Easy "One-Step" straps inserting.
- > Computer controlled operation monitoring system.
- > User self-adjustable front & rear strap width guiders to assure perfect strap alignment.
- > User changeable strap cutting blade and other wearing parts.
- > Optional hanger to reduce operation fatigue.

**2 YEAR
WARRANTY
BRUSHLESS MOTOR
AND ECU**

APPLICATIONS

Ideal strapping tool for various strapping jobs of heavy duty strapping such as heavy pallet consignment, paper, bricks, metal pipes and lumber.



SPECIFICATIONS

Power source	Rechargeable battery
Sealing type	Friction welding
Tension type	Automatic
Strap material	Polyester (PET) or Polypropylene (PP)
Strap width	13-16mm (4/8 - 5/8 inches) or 16 & 19mm (5/8 & 3/4 inches)
Strap thickness	PP: 0.75-1.05mm (.029-.04 inches) PET: 0.55-1.05mm (.022-.04 inches)
Sealing efficiency	80%+-5% of strap breaking strength (varies based on strap quality, remaining of battery power and set sealing time)
Sealing time adjustment	0.6-4.8 seconds
Tension force	Max. tension Kgs/ N (Tension performance varies based on strap specification and quality, and the remaining of battery power).
Weight	3.35Kgs./ 7.37Lbs.(Tool), 0.9Kgs./2Lbs.(Battery).
Dimensions	15.37" x 5.03" x 5.3"
Battery life	Up to 2000 charges of proper charging and ambient temperature
Strapping cycles	Fully charged battery support up to approximately 250 strapping cycles under max. tension setting and normal ambient temperature
Contents of package set	Each package set contains strapping tool, battery and adaptor.

MODELS

Model No.	Battery Charger Voltage	Fits Poly Strap	Strap Width		Strap Thickness		Maximum Tension	Sealing Efficiency	Dimension
			mm	inch	mm	inch			
SPZP26-6X	230V	PP	16	4/8-5/8	0.75-1.05	.029-.04	PET: From 90 kgs to 330 kgs	80+5%	Weight: Tool: 3.35kgs (7.37Lbs) Battery: 0.9kgs (2Lbs)
		PET	13-16	13-16	0.55-1.05	.022-.04			
SPZP26-9X		PP	16&19	5/8 & 3/4	0.75-1.05	.029-.04	PP : From 50 kgs to 180 kgs		
		PET			0.65-1.05	.026-.04			



AWARDS



2002 SYMBOL OF EXCELLENCE WINNER IN TAIWAN