



SPBS-4525

**Description:**

SPBS-45 series shrink tunnel adopts stainless steel heater and high power blowing motor for shrinking tunnel, characterized by quick heat-up, strong and even blowing. Both conveying speed and temperature of tunnel can be changed according to different sizes and output requirements of different objects.

**Features:**

1. Speed of conveying belt can be regulated at will by electric speed controller.
2. Overheating-proof for machine surface by adopting double insulation mechanism.
3. With temperature-resistant and heat-insulating cord fabric to be against heat loss.
4. Adopt the solid roller packed in thermo-stable silicone tube as conveying chain, which can stand heavy-duty object without deformation

**Application:**

SPBS-45 series shrink tunnel are applied to all kinds of shrink films, such as PVC, PP, POF.

<b>Parameters::</b>	<b>SPBS-4525</b>	<b>SPBS-4535</b>
<b>Voltage(V/Hz)</b>	3 Phase 380/50 or 3 Phase 220/60	
<b>Power (kw)</b>	9	
<b>Loading (kg)</b>	10	
<b>Max. Packing Size (L×W×H)(mm)</b>	700×400×200	700×400×300
<b>Speed (m/min)</b>	0~10	
<b>Tunnel Size (L×W×H)(mm)</b>	1000×450×250	1000×450×350
<b>External Dimensions (L×W×H)(mm)</b>	1300×715×1455	1300×715×1555
<b>Net Weight (kg)</b>	185	195